

FLOOR MOUNTED CHARGER		EUROPEAN STANDARD	AMERICAN STANDARD
PARAMETER	Product Name	44KW Dual Gun AC EV Charger	96A Dual Gun AC EV Charger
	Item No.	EE-ACH101-44-2A1	EU-ACH2A1-96
TECHNICAL INFORMATION	Power Input Cable	L1,L2,L3,N,PE	L1,L2,PE
	Rated Voltage	380V	120V-240V
	Rated Current	32A*2	48A*2
	Rated Power	44KW	/
INTERFACE	Plug Type	Type 2*2	Type 1*2
	Cable Length	5M (Customization Acceptable)	
	Housing Material	Electrolytic plate+Stainless Steel	
	LED Indicator Lamp	Optional	
	Screen	4.3 Inch Control Screen	
	Display Parameters	Charge Voltage, Charge Current, Charge Quantity, Fault Code	
	Charging Way	Plug And Charge	
COMMUNICATION	Ethernet	Optional	
	4G	Optional	
	OCPP	OCPP1.6J	
SAFETY	RCD	Type A +6mA DC	CCID20
	IP Rate	Connector IP54	
	Safety Protection	Emergency Stop/ Over Voltage Protection/ Under Voltage Protection/ Over Current Protection/ Leakage Current Protection/ Ground Protection/ Over Temperature Protection/ Short-circuit Protection/ Lightning Protection	
	Safety Standard	IEC/EN62752	UL2231
	Certification	CE/UKCA	ETL, CSA, ENERGY STAR
	Warranty	One Year	
INSTALLATION	Installing Type	Floor Mounted	
	Working Temperature	-25°C -50°C	
	Working Humidity	5%~95%	
	The Cooling Way	Natural Air Cooling	
	Dimension	1300mm*330mm*170mm	
	Net Weight	30KG	
	Gross Weight	43KG	

FLOOR MOUNTED CHARGER		EUROPEAN STANDARD	AMERICAN STANDARD
PARAMETER	Product Name	44KW AC EV Charger	64A AC EV Charger
	Item No.	EE-ACH101-44-2A2	EU-ACH2A2-64
TECHNICAL INFORMATION	Power Input Cable	L1,L2,L3,N,PE	L1,L2,PE
	Rated Voltage	380V	120V-240V
	Rated Current	32A*2	32A*2
	Rated Power	44KW	/
INTERFACE	Plug Type	Type 2*2	Type 1*2
	Cable Length	Charging Inlet	
	Housing Material	Electrolytic plate+Stainless Steel	
	LED Indicator Lamp	Optional	
	Screen	4.3 Inch Control Screen	
	Display Parameters	Charge Voltage, Charge Current, Charge Quantity, Fault Code	
	Charging Way	Plug And Charge	
COMMUNICATION	Ethernet	Optional	
	4G	Optional	
	OCPP	OCPP1.6J	
SAFETY	RCD	Type A +6mA DC	CCID20
	IP Rate	Connector IP54	
	Safety Protection	Emergency Stop/ Over Voltage Protection/ Under Voltage Protection/ Over Current Protection/ Leakage Current Protection/ Ground Protection/ Over Temperature Protection/ Short-circuit Protection/ Lightning Protection	
	Safety Standard	IEC/EN62752	UL2231
	Certification	CE/UKCA	ETL, CSA, ENERGY STAR
	Warranty	One Year	
INSTALLATION	Installing Type	Floor Mounted	
	Working Temperature	-25°C -50°C	
	Working Humidity	5%~95%	
	The Cooling Way	Natural Air Cooling	
	Dimension	1400mm*400mm*180mm	
	Net Weight	28KG	
	Gross Weight	40KG	

FLOOR MOUNTED CHARGER		EUROPEAN STANDARD	AMERICAN STANDARD
PARAMETER	Product Name	44KW Single Gun AC EV Charger	96A Single Gun AC EV Charger
	Item No.	EE-ACH101-22-2A3	EU-ACH2A3-48
TECHNICAL INFORMATION	Power Input Cable	L1,L2,L3,N,PE	L1,L2,PE
	Rated Voltage	380V	120V-240V
	Rated Current	32A	48A
	Rated Power	22KW	/
INTERFACE	Plug Type	Type 2	Type 1
	Cable Length	5M (Customization Acceptable)	
	Housing Material	Electrolytic plate+Stainless Steel	
	LED Indicator Lamp	Optional	
	Screen	4.3 Inch Control Screen	
	Display Parameters	Charge Voltage, Charge Current, Charge Quantity, Fault Code	
	Charging Way	Plug And Charge	
COMMUNICATION	Ethernet	Optional	
	4G	Optional	
	OCPP	OCPP1.6J	
SAFETY	RCD	Type A +6mA DC	CCID20
	IP Rate	Connector IP54	
	Safety Protection	Emergency Stop/ Over Voltage Protection/ Under Voltage Protection/ Over Current Protection/ Leakage Current Protection/ Ground Protection/ Over Temperature Protection/ Short-circuit Protection/ Lightning Protection	
	Safety Standard	IEC/EN62752	UL2231
	Certification	CE/UKCA	ETL, CSA, ENERGY STAR
	Warranty	One Year	
INSTALLATION	Installing Type	Floor Mounted	
	Working Temperature	-25°C -50°C	
	Working Humidity	5%~95%	
	The Cooling Way	Natural Air Cooling	
	Dimension	1300mm*330mm*170mm	
	Net Weight	30KG	
	Gross Weight	43KG	