

| FLOOR MOUNTED CHARGER |                     | EUROPEAN STANDARD                                                                                                                                                                                                      | AMERICAN STANDARD          |
|-----------------------|---------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------|
| PARAMETER             | Product Name        | 44KW Dual Gun AC EV Charger                                                                                                                                                                                            | 96A Dual Gun AC EV Charger |
|                       | Item No.            | EE-ACH101-44-2G2                                                                                                                                                                                                       | EU-ACP2G2-96               |
| TECHNICAL INFORMATION | Power Input Cable   | L1,L2,L3,N,PE                                                                                                                                                                                                          | L1,L2,PE                   |
|                       | Rated Voltage       | 380V                                                                                                                                                                                                                   | 120V-240V                  |
|                       | Rated Current       | 32A*2                                                                                                                                                                                                                  | 48A*2                      |
|                       | Rated Power         | 44KW                                                                                                                                                                                                                   | /                          |
| INTERFACE             | Plug Type           | Type 2*2                                                                                                                                                                                                               | Type 1*2                   |
|                       | Cable Length        | 5M (Customization Acceptable)                                                                                                                                                                                          |                            |
|                       | Housing Material    | Electrolytic plate+Stainless Steel                                                                                                                                                                                     |                            |
|                       | LED Indicator Lamp  | Support                                                                                                                                                                                                                |                            |
|                       | LED Screen          | 4.3 Inch Control Screen+43 Inch LCD Advertising Screen                                                                                                                                                                 |                            |
|                       | Display Parameters  | Charge Voltage, Charge Current, Charge Quantity, Fault Code                                                                                                                                                            |                            |
|                       | Charging Way        | Plug And Charge                                                                                                                                                                                                        |                            |
| COMMUNICATION         | Ethernet            | Optional                                                                                                                                                                                                               |                            |
|                       | 4G                  | Optional                                                                                                                                                                                                               |                            |
|                       | OCPP                | OCPP1.6J                                                                                                                                                                                                               |                            |
| SAFETY                | RCD                 | Type A +6mA DC                                                                                                                                                                                                         | CCID20                     |
|                       | IP Rate             | Connector IP54                                                                                                                                                                                                         |                            |
|                       | Safety Protection   | Emergency Stop/ Over Voltage Protection/ Under Voltage Protection/ Over Current Protection/ Leakage Current Protection/ Ground Protection/ Over Temperature Protection/ Short-circuit Protection/ Lightning Protection |                            |
|                       | Safety Standard     | IEC/EN62752                                                                                                                                                                                                            | UL2231                     |
|                       | Certification       | CE/UKCA                                                                                                                                                                                                                | In Processing              |
|                       | Warranty            | One Year                                                                                                                                                                                                               |                            |
| INSTALLATION          | Installing Type     | Floor Mounted                                                                                                                                                                                                          |                            |
|                       | Working Temperature | -25°C -50°C                                                                                                                                                                                                            |                            |
|                       | Working Humidity    | 5%~95%                                                                                                                                                                                                                 |                            |
|                       | The Cooling Way     | Natural Air Cooling                                                                                                                                                                                                    |                            |
|                       | Dimension           | 1700mm*720mm*264mm                                                                                                                                                                                                     |                            |
|                       | Net Weight          | 145.5kg                                                                                                                                                                                                                |                            |
|                       | Gross Weight        | 160kg                                                                                                                                                                                                                  |                            |