

Model G EV Charger Data Sheet			
FLOOR MOUNTED CHARGER		EUROPEAN STANDARD	AMERICAN STANDARD
PARAMETER	Product Name	44KW Dual Gun AC EV Charger	96A Dual Gun AC EV Charger
	Item No.	EE-ACH101-44-2G2	EU-ACP2G2-96
TECHNICAL INFORMATION	Power Input Cable	L1,L2,L3,N,PE	L1,L2,PE
	Rated Voltage	380V	120V-240V
	Rated Current	32A*2	48A*2
	Rated Power	44KW	/
INTERFACE	Plug Type	Type 2*2	Type 1*2
	Cable Length	5M (Customization Acceptable)	
	Housing Material	Electrolytic plate+Stainless Steel	
	LED Indicator Lamp	Support	
	LED Screen	4.3 Inch Control Screen+43 Inch LCD Advertising Screen	
	Display Parameters	Charge Voltage, Charge Current, Charge Quantity, Fault Code	
	Charging Way	Plug And Charge	
COMMUNICATION	Ethernet	Optional	
	4G	Optional	
	OCPP	OCPP1.6J	
SAFETY	RCD	Type A +6mA DC	CCID20
	IP Rate	Connector IP54	
	Safety Protection	Emergency Stop/ Over Voltage Protection/ Under Voltage Protection/Over Current Protection/ Leakage Current Protection/ Ground Protection/Over Temperature Protection/ Short-circuit Protection/ Lightning Protection	
	Safety Standard	IEC/EN62752	UL2231
	Certification	CE/UKCA	In Processing
	Warranty	One Year	
INSTALLATION	Installing Type	Floor Mounted	
	Working Temperature	-25℃ -50℃	
	Working Humidity	5%~95%	
	The Cooling Way	Natural Air Cooling	
	Dimension	1700mm*720mm*264mm	
	Net Weight	145.5kg	
	Gross Weight	160kg	