

Model F EV Charger Data Sheet			
WALL-MOUNT EV CHARGER		EUROPEAN STANDARD	AMERICAN STANDARD
PARAMETER	Product Name	44KW Dual Gun AC EV Charger	96A Dual Gun AC EV Charger
	Item No.	EE-ACH101-44-2FX	EU-ACH2FX-96
TECHNICAL INFORMATION	Power Input Cable	L1,L2,L3,N,PE	L1,L2,PE
	Rated Voltage	380V	120V-240V
	Rated Current	32A*2	48A*2
	Rated Power	44KW	/
FUNCTION	Plug Type	Type 2*2	Type 1*2
	Cable Length	5M	
	Housing Material	Stainless Steel	
	LED Indicator Lamp	Support	
	LED Screen	4.3 Inch Touch Screen	
	Display Parameters	Charge voltage, Charge current, Charge Quantity, Fault code	
	Charging Way	RFID/ Touch screen to action	
COMMUNICATION	Ethernet	Optional	
	4G	Optional	
	OCPP	OCPP1.6J	
SAFETY	RCD	Type A +6mA DC	CCID20
	IP Rate	Connector IP65	
	Safety Protection	Over Voltage Protection/Under Voltage Protection/Over Current Protection/ Leakage Current Protection/Ground Protection/Over Temperature Protection	
	Safety Standard	IEC/EN62752	UL2231
	Certification	CE/UKCA	ETL, CSA, ENERGY STAR
	Warranty	One Year	
INSTALLATION	Installing Type	Column Mounted(Floor Mounted) or Wall Mounted Install Optional	
	Working Temperature	-25°C - 50°C	
	Working Humidity	5%~95%	
	The Cooling Way	Natural Air Cooling	
	Dimension	355*250*93mm	
	Net Weight	24.5kg	
	Gross Weight	25.6kg	